

# Homework 6

## Build Systems

Assigned: Friday, February 12, 11:00AM

**Due: Friday, February 19, 11:00AM (Hard Deadline)**

### Submission Instructions

Submit this assignment on [Gradescope](#). You must submit every page of this PDF. We recommend using the free online tool [PDFescape](#) to edit and fill out this PDF. You may also print, handwrite, and scan this assignment.

**Even if there are not questions to answer on the first page, please still submit every page of this PDF.**

There may multiple answers for each question. If you are unsure, state your assumptions and your reasoning for why you think your answer makes sense.

For this assignment, we will experiment in the EECS 280 W15 repository you created for Homework 4.

## 1 Expressing Dependencies

1. Run `make` to build everything.
2. Run `make` again (nothing happens).
3. Edit `p2.cpp` and make a change (add a comment or something).
4. Run `make` again.
5. Edit `p2.h` and make a change (add a comment or something).
6. Run `make` again.

Why did `make` rebuild things after step 4 but not after step 6? Why is this a problem?

Rewrite the rule for `simple_test` so that `make` rebuilds correctly for any changes you make:<sup>1</sup>

*Think this is a pain? Check out the advanced homework for a BetterWay<sup>TM</sup>.*

## 2 From Build Engine to Rules Engine

Makefiles are often asked to do more than simply build your software. A common example is a rule named `clean` that deletes everything built by the Makefile.

1. Run `make` to build everything.
2. Run `make clean` to delete everything that was built.
3. Run `make` to build everything.
4. Run `touch clean`
5. Run `ls` (do you understand what `touch` does?)
6. Run `make clean`

Why did `make` run the `clean` rule after step 2 but not after step 5?

What flag can you pass to `make` so that it unconditionally “builds” the `clean` target?

```
make -__ clean
```

Describe how to fix the Makefile so that fake targets like `clean` work correctly.

---

<sup>1</sup>You do not need to worry about system header files

### 3 Removing Duplicated Effort

Notice that currently the `all` target and the `test` target have the same list of dependencies.

List all the changes you have to make to the Makefile so that the `test` target correctly depends on the `all` target in all cases.

### 4 Anything Special about All?

Currently, if you just type `make`, `make` will run `make all`. One might wonder why `make` chooses the `all` goal by default. While you could look this up, we are computer *scientists*. Make changes to the Makefile until you are confident that you understand how `make` chooses the default goal.

Describe the experiments you ran in order to determine what target `make` builds by default.

## 5 Pulling Some Pieces Together

Option 3 from Question 3 on Homework 3 (during week 3!) noted:

First cool thing that happened: Yes, you can run make without any Makefile anywhere. We'll cover how that happened during build-system week.

First let's get a simple environment set up and try some things out:

```
> mkdir /tmp/wk6 && cd $_
> echo -e '#include <stdio.h>\n\nint main() {\n\tprintf("Howdy\\n");\n\treturn 0;\n}\n' > hello.c
> make
> make hello
> ./hello
```

Does make clean work? Why not?

Now try

```
> rm hello
> make -r hello
```

What does the `-r` flag do?

Next try

```
> make CFLAGS=-O3 hello
```

What changed when hello was built this time?

Finally run

```
> make hello -p | less
```

**Find the built-in rule that runs to create “hello” from “hello.c” and copy it here:**

Now let's add an additional file to the mix, only a C++ file this time:

(This example uses a [special shell syntax](#) for easily writing multiple lines to a shell command)

```
> cat << MARKER > wazzup.cpp
#include <iostream>

int main() {
    std::cout << "Wazzup?" << std::endl;
    return 0;
}
MARKER
> cat wazzup.cpp
```

**Using what you have learned, write a single make command (i.e. only call make once) that, without a Makefile, will build both “hello” and “wazzup”, but builds hello optimized for speed (`-O3`) and wazzup optimized for size (`-Os`).**